



## 3 Port Multi AV to HDMI Presentation Switch

No.: 38272

Autoswitching Converter

### Description

Multi interface video switch for connecting various source devices to an HDMI display or projector - ideal for presentation, conference and education installations

Supports direct conversion (no-scaling) of DisplayPort and VGA with Audio to HDMI

Supports resolutions up to 4K Ultra HD 3840 x 2160p 60Hz, HDCP 2.2 compatible

Easy switching by IR, Push Button and Auto-Sensing

2 Year Warranty

Designed to connect multiple source devices with HDMI display equipment this Presentation Switch features DisplayPort, HDMI and VGA inputs, which are directly converted to HDMI at resolutions up to 4K Ultra HD, without scaling. In addition to support for 4K Ultra HD resolutions the Switch also supports HDCP 2.2 protected signals and both DTS and Dolby Digital audio pass-through making it suitable for both PC and AV applications.

Switching between the connected source devices can be completed using the Presentation Switch's Auto-Sensing function which automatically switches to a newly connected/powered on device, via the front panel push buttons or using the supplied IR remote control. IR codes are also provided to enable integration of the switch within a larger AV installation. The switch is supplied with mounting brackets which allow it to be conveniently installed according to the installation environment.

The Presentation Switch is an ideal addition to any meeting or conference room, lecture hall or auditorium. For added flexibility the Switch can be used with LINDY's range of HDMI Extenders, to reach remote displays and projectors.

Please Note : Using the auto-sensing switching feature with the DisplayPort input requires the use of the supplied all pins connected 20 Pin DisplayPort cable between the source PC or Notebook and the switch.

### Technical details

#### Specifications

AV Interface: HDMI

Interface Standard: HDMI 2.0

Supports Bandwidth: 18 Gbps

Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit

HDCP Support: 2.2

Supported Audio: Audio Pass-through, Stereo Audio

Separate Audio Ports: 3.5mm

IR Support: -

CEC Support: -

Serial Interface: -

Special Features: -

#### Connectors

Input: DisplayPort (Female), HDMI (Female), VGA (Female), 3.5mm (Female)

Output: HDMI (Female)

Control: -

Power: 5.5/2.5mm DC socket

#### **Physical Properties**

Dimensions WxDxH: 155x72x25mm (6.1x2.83x0.98in)

Housing Material: Metal

Net Weight: 0.38kg (0.84lb)

Operating Temperature: 0°C - 40°C (32°F - 104°F)

Storage Temperature: -20°C - 60°C (-4°F - 140°F)

Humidity: 0 - 60% RH (non-condensing)

Power Requirements: 5VDC 1A

Colour: Black

#### **Miscellaneous**

Packaging Type: Carton box

Packaging Dimensions: 164x77x165mm (6.46x3.03x6.5in)

Gross Weight: 0.605kg (1.33lb)

Warranty (Years): 2

Product Compliance: CE, FCC, RoHS & REACH

#### **Package Contents**

DP/HDMI/VGA to HDMI Presentation Switch

IR Remote Control with 1 x CR2025 battery

DisplayPort Cable

2 x Mounting brackets

Multi-Country Power Supply (EU, UK, US & AUS)

Lindy Manual

#### **Purchasing Information**

No.: 38272

EAN: 4002888382724